

Tubo hidráulico Inox-316L

TOLERANCIAS

ø ext. 6-42 mm, DIN 2391/EN 10305-1

ø ext. mm.	Tolerancias ø ext. mm.	Espesor %
6-30	+/- 0.08	+/- 10
32-40	+/- 0.15	+/- 10
42	+/- 0.20	+/- 10

ø ext. <6 mm. tolerancias s/ASTM A632

ø ext. mm.	Tolerancias ø ext. mm.	Espesor %
<6 - 4.76	+ 10 / -0	+/- 10
<4.76 - 2.38	+ 0.08 / -0	+/- 10
<2.38	+ 0.05 / -0	+/- 10

316/316L a partir 42 mm.

Ext ± 0,50% (mínimo ± 0,1 mm (D4))

Pared ± 10% (mínimo ± 0,2 mm(T3))

NORMAS STANDARD

(TP 316/316L)

DIN 17458, TC1

NFA 49-117

ASTM A213-AW (average wall)

ASTM A269

NACE MR0175/ISO 15156

PED 97/23/EC

EN 10216-5 TCI

OD<6 mm acc to A632

ø ext. mm.	espesor mm.	Peso kg/m	Calidad 3116/316L EN 1.4435	ø ext. mm.	espesor mm.	Peso kg/m	Calidad 3116/316L EN 1.4435
6	1	0,125	●	22	1,5	0,769	○
	1,5	0,169	○		2	1,000	●
8	1	0,175	●	25	2	1,150	●
	1,5	0,244	●		2,5	1,407	●
	2	0,300	●		3	1,650	○
10	1	0,225	●	28	1,5	0,994	○
	1,5	0,319	●		2	1,300	○
	2	0,400	●		2,5	1,594	○
12	1	0,275	○	30	2,5	1,719	○
	1,5	0,394	●		3	2,025	●
	2	0,500	●		4	2,601	○
14	1	0,325	○	35	2	1,650	○
	2	0,600	●		3	2,401	○
15	1	0,350	○	38	2	1,800	○
	1,5	0,506	○		3	2,626	○
	2	0,650	●		4	3,401	○
16	1	0,375	○		5	4,126	○
	1,5	0,544	○	42	2	2,000	○
	2	0,700	●		3	2,926	○
	2,5	0,844	○	50	5	5,627	●
18	1	0,425	○				
	1,5	0,619	○				
	2	0,800	●				
20	1,5	0,694	○				
	2	0,900	●				
	2,5	1,094	●				
	4	1,600	○				

● En stock ○ 10 días

